



VXX Series Triplex Plunger Pump

VXX-B 130/220
VXX-B 160/180
VXX-B 200/150

- Die-cast aluminium CRANKCASE with reinforcement ribs.
- HEAD in nickel-plated brass with reinforced stressed areas.
- Forged steel reinforced CRANKSHAFT.
- Spherical roller BEARINGS for self-alignment of crankcase, crankshaft and connecting rods; no shimming required in case of bearing replacement.
- Heavy duty bronze CONNECTING RODS.
- Solid ceramic PLUNGERS with very high finishing surface.
- Double V-shaped fabric-reinforced NBR high pressure SEALS for longer seal life and less maintenance.
- U-shaped fabric-reinforced NBR low pressure SEAL for better sealing capabilities at low pressures.
- Stainless steel VALVES with high efficiency spherical design.

MODEL	RPM	FLOW RATE		PRESSURE			POWER		WEIGHT
		l/min	GPM	bar	MPa	PSI	HP	kW	
VXX-B 130/220	1000	130	34.4	220	22	3190	73.3	53.9	58.7
VXL-6 16\$/% \$	1000	160	42.3	180	18	2610	73.8	54.2	58.7
VXL-B 200/150	1000	200	52.8	150	15	2175	76.9	56.5	58.4

